

1.

Exterior Lines, T.6 S., R.33 E., W. M.
 As surveyed by Frank W. Campbell, U.S. Deputy Surveyor,
 Under Contract No. 468,
 Dated April 12, 1883.

Chains From the Cor. to Tps. 6 & 7 S., Rs. 33 & 34 E., I run
 W. on random line bet. said Tps.
 Var. 20° E.

I set temp. half mile & mile Cors., at each 40 & 80 chs.
 and find the Tp. line to be 5 miles, 76 chs. & 17 lks.
 and the falling to be 200 lks. S. of Cor. to Tps. 6 & 7
 S., Rs. 32 & 33 E.

The correction for the true line will therefore be 33 1/3
 lks. N. and its course will be S. 89° 46' E.

From the Cor. to Tps. 6 & 7 S., Rs. 32 & 33 E., which is
 a post, 5 ins. sq., marked

T 6 S S 36 on N.W.
 R 32 E S 1 on S.W.
 S 31 on N.E. and
 R 33 E S 6 on S.E. faces, with
 6 notches on each edge,

from which

A tamarack, 18 ins. diam., brs. N. 8° W., 34 lks. dist.,
 marked T 6 S R 32 E S 36 B T.

A pine, 18 ins. diam., brs. N. 78° E., 31 lks. dist.,
 marked T 6 S R 33 E S 31 B T.

A pine, 24 ins. diam., brs. S. 34° E., 114 lks. dist.,
 marked T 7 S R 33 E S 6 B T.

A pine, 24 ins. diam., brs. S. 40° W., 28 lks. dist.,
 marked T 7 S R 32 E S 1 B T.

Thence I run
 S. 89° 46' E. on a true line bet. Secs. 6 & 31.
 Var. 20° E.

25.50 Creek, 8 lks. wide, runs S.W.

36.17 Set basalt stone, 13 x 10 x 10 ins., 8 ins. in ground, for
 1/2 Sec. Cor., marked 1/2 on N. face, from which

A pine, 30 ins. diam., brs. S. 45° E., 11 lks. dist.,
 marked 1/2 S B T.

A pine, 36 ins. diam., brs. N. 20° E., 43 lks. dist.,
 marked 1/2 S B T.

76.17 Set basalt stone, 16 x 13 x 10 ins., 8 ins. in ground, for