

1.

Exterior Lines, T 6 S., R. 34 E., W.M.
 As surveyed by Frank W. Campbell, U.S. Dept. Surveyor,
 Under Contract No. 468,
 Dated April 12, 1883.

Chains

From the Cor. to Tps. 6 & 7 S., Rs., 34 & 35 E., I run
 W. on random line bet. said Tps., the variation of my com-
 pass being 20°E., I set the temp. $\frac{1}{2}$ mile and mile Cors.,
 at each 40 & 80 chs. and find the Tp. line to be 5 miles
 76 chs. and 2 lks. long, and the falling to be 252 lks.
 S. of the Cor. to Tps. 6 & 7, Rs. 33 & 34 E.
 The correction for the true line will, therefore be 43 lks.
 per mile and its course will be S. 89°42'E.

July 14, 1883.

From the Cor. to Tps. 6 & 7 S., Rs. 33 & 34 E., I run
 S. 89°42'E. on true line bet. Secs. 6 & 31.

Var. 20°E.

2.75 Creek, 8 lks. wide, runs S.W.

40.00 Set post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$
 Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which
 A pine, .5 ins. diam., brs. S. 20°W., 9 lks. dist.,
 marked $\frac{1}{4}$ S B T.
 A fir, 15 ins. diam., brs. N. 40°E., 43 lks. dist.,
 marked $\frac{1}{4}$ S B T.

40.08 Brook, 3 lks. wide, runs N.W.

76.02 Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
 Cor. to Secs. 5, 6, 31 & 32, marked
 T 6 S S 32 on N.E.
 R 34 E S 5 on S.E.
 T 7 S S 6 on S.W. and
 S 31 on N.W. faces, with
 1 notch on W. and
 5 notches on E. edges,
 from which
 A pine, 6 ins. diam., brs. N. 38°E., 16 lks. dist.,
 marked T 6 S R 34 E S 32 B T.
 A pine, 8 ins. diam., brs. S. 20°E., 7 lks. dist.,
 marked T 7 S R 34 E S 5 B.T.
 A pine, 10 ins. diam., brs. S. 31°W., 3 lks. dist.,
 marked T 7 S R 34 E S 6 B.T.