

## PLAT AND RECORD OF SURVEY No. 160

Request of Jo<sup>l</sup>. Blanchett et al, May 26. 1893.

Assisted by Albert E. Bowles and Edgar Thomson, sworn chmns. I commence at cor. to sec. 35<sup>th</sup> 36 on S. bdy. of Tp. 17 N. R. 30 E. which is a decayed triangular post, lying on mound with trench, post mkd. correctly.

Set, in the center of this mound, a stone 25 x 22 x 14 ins. 20 ins. in ground, for cor. to sec. 35<sup>th</sup> 36 T. 17 N. R. 30 E. mkd. 1 notch on E and 5 notches on W. with + on top. Using a theodolite, I run thence on random base line.

400 Descend.

W. 22° E.

400 Foot of hill

570 Contr. of cañon N. Ascend steep hill

827 Stone cor. mkd cc on S. 6 notches on E and W faces, set firmly in <sup>(ground)</sup>

1350 Summit - Descend.

2090 Ravine, course N.E. Ascend.

2640 Set temp.  $\frac{1}{4}$  sec. cor. No traces of original cor.

3467 " "  $\frac{1}{4}$  " " on N. bdy. sec. 1 T. 17 N. R. 30 E.

5280 " " cor. to sec. 34<sup>th</sup> 35 T. 17 N. R. 30 E. - No traces of original

825 Stone mkd cc and HAMAK, lying on ground

2400 Descend - Maaki's house about 500 ft S. of line

2640 Set temp  $\frac{1}{4}$  sec. cor.

2659 Int. N. <sup>th</sup> S. line 32 ft. N. of  $\frac{1}{4}$  sec. cor. on S. bdy sec. 34, which is a stone, which Mr. Jo<sup>l</sup>. Blanchett, present, says he put in the place of the original post, about 8 years ago. This cor. is verified by J. P. Westler, S. G. Thomson, Jo<sup>l</sup>. Shuets, Jacob Klotz, Jno Stanton and Benj Selling. At true cor. pt. I set a basalt stone 26 x 13 x 9 ins. 16 ins. in ground, for  $\frac{1}{4}$  sec. cor. mkd.  $\frac{1}{4}$  on N. and + on top

For  $\frac{1}{4}$  sec. cor. on N. bdy, of sec. 1 T. 17 N. R. 30 E. I find true point by proportions, and set a stone 13 x 12 x 7 ins. 10 ins. in ground, mkd.  $\frac{1}{4}$  on S. and + on top, near summit, in E. <sup>th</sup> W. lane, and opposite fence runing S.

I make careful measure, and proportion of distances, and at proper points on true Base line, I set stone corners, as follows.  
In  $\frac{1}{4}$  sec. cor. on S. bdy. of sec. 35 T. 17 N. R. 30 E. a stone 14 x 10 x 4 ins. 12 ins. in ground, mkd.  $\frac{1}{4}$  on N. face, notched on top, in very old & W. furrows, on E. face of hill.

Courses.	Degrees.	Minutes.	Chains.	Links.
<p>The cor. to sec. 35<sup>th</sup> &amp; 34<sup>th</sup> T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup>, which is a stone 17x16x9 ins. 12 ins. in ground mkd. 5 notches on E and W. sides and + on top.</p> <p>The <math>\frac{1}{4}</math> sec. cor. on S. bdy. sec. 33, which is a stone 17x14x8 ins. 14 ins. in ground mkd. <math>\frac{1}{2}</math> on N. and + on top</p> <p>Survey commenced May 25<sup>th</sup> and ended May 26<sup>th</sup> 1893.</p> <p>Jno. C. Arnold, County Surveyor.</p>				

Corners set in a survey for J. F. Houcke July 13<sup>th</sup> & 14<sup>th</sup> 1893.

The  $\frac{1}{4}$  sec. cor. on N. bdy. of sec. 5. T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup>, which is a smooth boulder 14x8x4 ins. 12 ins. in ground, in angle of fences E. S.  $\frac{1}{2}$  W. on E side of angle in corner S.  $\frac{1}{2}$  E W.

The  $\frac{1}{4}$  sec. cor. bet. sec. 5<sup>th</sup> & 6<sup>th</sup> T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup>, which is a slatted basalt stone 22x15x3 ins. mkd.  $\frac{1}{2}$  on W. on SE hill side 42 feet west of a ravine course about south, stone set 20 ins. in ground.

Jno. C. Arnold, County Surveyor.

The  $\frac{1}{4}$  sec. cor. bet. sec. 8<sup>th</sup> & 9<sup>th</sup> T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup> is a basalt stone 12x8x5 ins. 8 ins. in ground mkd.  $\frac{1}{4}$  on W. face, set in center of original mound, stone mkd. also + on top

The  $\frac{1}{4}$  sec. cor. bet. sec. 4<sup>th</sup> & 9<sup>th</sup> T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup> is a basalt stone 10x9x8 ins. 8 ins. in ground mkd.  $\frac{1}{4}$  on W. face and + on top, set on true line midway between sections as per original notes. The two last described corners were set in a subdivisional survey of sec. 9. T<sup>h</sup> 17<sup>n</sup>. R 32<sup>e</sup>

Cor. to sec. 4. S. 8<sup>th</sup> & 9<sup>th</sup> is a stone, with 4 notches on E.  $\frac{1}{4}$  sec. cor. on S. bdy. sec. 9. is a stone 10x6x6 ins. mkd.  $\frac{1}{2}$  on N. & 7<sup>th</sup> & 8<sup>th</sup> T<sup>h</sup>

Jno. C. Arnold, County Surveyor,  
Umatilla Co. Oregon.